



Product name :
5702 Serie



	<p>Description : Fuse-Holder Lead with ends to be defined.</p>	
<p>Electric protection : From 500 V CAT II / 500 V CAT III to 600 V CAT II / 600 V CAT III, reinforced insulation, pollution degree 2, up to 20 A.</p>	<p>Color : Red, black.</p>	<p>Cable type : PVC 1.00 mm² (AWG17) ou silicone 1.00 mm² (AWG17).</p>
<p>Lenght : 50 cm (20 "), 100 cm (39 "), 150 cm (59 "), 200 cm (79 ").</p>	<p>Detail : Numerous versions to be defined from fuse-holder and wire end versions. 500 V CAT II / 500 V CAT III, reinforced insulation, 10 mm x 38 mm (13 / 32 " x 1 / 2 ") standard fuse-holder version including fuse 2 A or 6 A or 10 A or 16 A or 20 A. 600 V CAT II / 600 V CAT III, reinforced insulation, 10 mm x 38 mm (13 / 32 " x 1 / 2 ") class CC fuse-holder version including fuse 2 A or 6 A or 10 A or 15 A or 20 A. Straight 4 mm banana (male) plug end version, right-angle 4 mm banana (male) plug end version, stacking 4 mm banana (male) plug end version, straight 4 mm banana (female) jack end version, etc ...</p>	

WWW.ELECTROPJP.COM - Electro-pjp 13, rue de Madrid, 39500 TAVAUZ - Tel : +33 3 84 82 13 30 FAX : 33 3 84 82 40 48